

MOL Dynamic Transit 10W-40

universal motor oil



MOL Dynamic Transit 10W-40 is a universal engine oil composed of mineral and synthetic oils produced using modern oil refining processes, using a balanced system of additives that ensures high engine oil performances in automobiles and in commercial motor vehicles. It includes components that modify the flow characteristics. It meets the requirements of the wide range of performance levels of engine manufacturers, as well as the most stringent US and European specifications for diesel engine oils. It is particularly recommended for Euro III, as well as for Euro IV and Euro V commercial vehicle engines which do not have a diesel particulate filter.

Application



Conventional gasoline or diesel, naturally aspirated or turbocharged commercial vehicles and passenger cars

Mixed vehicle fleet

Commercial vehicles and buses equipped with EGR and SCR systems

Short and long haul bus and commercial vehicle engines

Engines in mining, construction and agricultural machines, of equipment used for moving materials

Railway and ship diesel engines operating at low speed and high load

Features and benefits

Extreme cold flow properties

Provides easy start-up, even in extreme cold, to extend the life of the car battery

Extremely long oil lifetime

Frequency of downtimes, operational costs, and environmental impact can be reduced

Universal

Wide range of applicability enables reduction of the number of lubricating oils

Exceptional thermal and oxidation stability

Resists the ageing process and deposit formation, even at high operating temperatures, giving long oil lifetimes and reduced maintenance costs

Excellent shear stability

Maintains its favourable properties for a long period even under heavy loads and shear stresses

High-level reserve of alkalinity

Persistent acid neutralization, giving a long oil drain interval

Excellent soot handling

Protection against soot deposits and bore polishing

MOL Dynamic Transit 10W-40

universal motor oil



Specifications and approvals

Viscosity grade: SAE 10W-40
API CI-4
MB-Approval 228.3
MAN M 3275-1
Volvo VDS-3
Tatra TDS 30/12
Renault RLD-2
MTU Type 2
Mack EO-N
ACEA E7
Global DHD-1
Caterpillar ECF-2
MACK EO-M Plus
DDC 93K215
Deutz DQC III-10

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,872
Kinematic viscosity at 40°C [mm ² /s]	97,1
Kinematic viscosity at 100 °C [mm ² /s]	14,4
Viscosity index	153
Pour point [°C]	-39
Flash point (Cleveland) [°C]	230
Base number (BN) [mg KOH/g]	10,1

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

MOL Dynamic Transit 10W-40

universal motor oil



Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13100124	MOL Dynamic Transit 10W-40 X1L	1 l plastic bottle
13100125	MOL Dynamic Transit 10W-40 X4L	4 l plastic can
13301971	MOL Dynamic Transit 10W-40 X10L	10 l plastic can
13300390	MOL Dynamic Transit 10W-40 20LA	20 l plastic can
13100126	MOL Dynamic Transit 10W-40 50KG	60 l steel drum
13100127	MOL Dynamic Transit 10W-40 180KG	216.5 l steel drum
13100123	MOL Dynamic Transit 10W-40 860KG	IBC (for order only)
13300689	MOL Dynamic Transit 10W-40 860KG R1W	IBC (for order only)
13300285	MOL Dynamic Transit 10W-40	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.