

EVOX Premium Ready -35

coolant, ready to use



EVOX Premium Ready -35 is a pink coloured ready to use monoethylene-glycol based coolant liquid, produced with organic additive technology (OAT), it is free from nitrites, amines, phosphates, borates and silicates, and is suitable for filling the cooling systems of internal combustion engines. EVOX Premium Ready -35 can be mixed with other monoethylene-glycol and monopropylene-glycol based antifreeze coolants without limitation.

Application



Cooling systems of passenger and commercial vehicles, agricultural and construction machines and stationary gas engines

Cooling systems containing cast iron, aluminium and copper parts

Features and benefits

Good corrosion protection

Forms a stable protective film on the inner surface of the cooling system to ensure a long lifetime

Application specific composition

Protection against cavitation and sludge sedimentation

Compatible with construction materials

There's no damage to the plastic and rubber parts of the cooling system

EVOX Premium Ready -35

coolant, ready to use



Specifications and approvals

BS 6580:2010
ASTM D 3306
ASTM D 6210
Saab B 040 1065
VW/Audi/Seat/Skoda TL 774-D (VW code G12)
VW/Audi/Seat/Skoda TL 774-F (VW code G12 Plus)
MB 325.3
MB 326.3
Ford WSS-M97B44-D
MAN 324 Typ SNF
MAN D36 5600
CNH MAT 3624
MTU MTL 5048
Fendt
Caterpillar 0199-99-2091/12.
Caterpillar MAK A4.05.09.01
Caterpillar GCM34
Cummins CES 14439
Cummins IS series u N14
Mack 014 GS 17009
Jenbacher TI 1000-0201
MWM 0199-99-2091/12
Fiat 9.55523
Isuzu
Mitsubishi MHI
Hitachi
Liebherr MD1-36-130
Deutz DQC CB-14
Jaguar CMR 8229
STJLR 651.5003
SKODA 61-0-0257
SACM Diesel DLP799861
Kobelco
Komatsu 07.892 (2009)
Van Hool
Valtra
Claas
DAF 74002
Detroit Diesel Power Cool Plus
Deutz 0199-99-1115/6
Foton Q-FPT 2313005-2013
GM 6277M
John Deere JDMH5
Renault 41-01-001/-S Type D
Volvo Trucks 128 6083/002
Waukesha

EVOX Premium Ready -35

coolant, ready to use



Properties

Properties	Typical values
Appearance	pink
pH value	8,7
Density at 20 °C [kg/m ³]	1070
Freezing point [°C]	-39
Alkalinity [ml 0,1M HCl/10 ml]	2,7
Boiling point [°C]	110
Refractive index at 20 °C	1,3860

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Should be stored in its original packaging with airproof sealing, separately from foods, in a place protected against water and sunshine, locked away from children.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: -35°C - +30°C

Ordering information

Custom Tariff Number 38200000

SAP code and packaging:

19010055 EVOX Premium Ready -35 220KG

216.5 l steel drum (for order only)

19010379 EVOX Premium Ready -35 1100KG

IBC (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.