

MOL Farm STOU 10W-40

universal tractor oil



MOL Farm STOU10W-40 is a STOU type universal tractor oil produced from synthetic and highly refined mineral oil, using a complex additive system that meets the needs of tractors.

Application



Torque converters, capable of shifting gears under load (John Deere Direct Drive, Powershift), and drive elements of agricultural and construction machines

AGCO (Fendt) Vario gearboxes

Engines of tractors and self-propelled agricultural machines, for which the OEM specification is listed in the Specifications and Approvals section

Hydrostatic drives

Features and benefits

Excellent wear protection

Optimal friction characteristics

Excellent corrosion protection

Good thermal and oxidation stability

Improved cold flow properties

Long gear lifetime, giving reliable operation

Wet breaks and clutches operate silently and judder-free

Long-term protection against surface damage, even in the presence of moisture

No deposit or sludge formation
Reliable operation, so reduced operational costs

Reliable operation even at low temperatures

Specifications and approvals

Viscosity grade: SAE 10W-40
ACEA E3-96 Issue 4
API CG-4
API GL-4
Ford ESN M2C159-B/C
Caterpillar TO-2
ZF TE-ML 06B
ZF TE-ML 06C
ZF TE-ML 07B
Allison C-4
John Deere JDM J20C
John Deere JDM J27
Massey-Ferguson M1145
Massey-Ferguson M1144
White-Farm Q-1826
Eaton (Vickers) M-2950-S
Eaton (Vickers) I-280-S

MOL Farm STOU 10W-40

universal tractor oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,872
Kinematic viscosity at 40°C [mm ² /s]	88,4
Kinematic viscosity at 100 °C [mm ² /s]	13,0
Viscosity index	146
Pour point [°C]	-42
Flash point (Cleveland) [°C]	220

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13300365	MOL Farm STOU 10W-40 10LA	10 l plastic can (for order only)
13301233	MOL Farm STOU 10W-40 25L	25 l plastic can (for order only)
13100028	MOL Farm STOU 10W-40 50KG	60 l steel drum
13300010	MOL Farm STOU 10W-40 170KG	216.5 l steel drum
13300305	MOL Farm STOU 10W-40 860KG R1W	IBC (for order only)
13301232	MOL Farm STOU 10W-40	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.