



Gazpromneft Motor Oil 40, 50 and 60

Passenger Vehicle Engine Oils

Gazpromneft Motor Oil primarily intended for use in gasoline automotive engines of passenger cars, commercial vehicles and farm equipment. They've effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity and reduce wear. Specially engineered for hot climate conditions.

Applications

- Gasoline and diesel engines requiring oil with API SC/CA standards
- Older engine technologies
- Cars, vans, small trucks, light commercial vehicles and farm equipment

Features	Advantages and Potential Benefits
Wear protection	Provides efficient lubrication over a wide range of hot operating conditions
Thermal and oxidation stability	Resists oil thickening during whole drain interval
Detergent and dispersant properties	Control of high temperature deposits formation to prevent sludge and keep engine cleaner

Recommendations

- API SC/CA

Typical Characteristics

Properties	Method	Gazpromneft Motor Oil 40	Gazpromneft Motor Oil 50	Gazpromneft Motor Oil 60
SAE Viscosity Grade	SAE J300	40	50	60
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,9	18,5	24,6
Flash Point (COC), °C	ASTM D92	248	254	260
Pour Point, °C	ASTM D97	-16	-13	-12
Total Base Number, mg KOH/g	ISO 6619	4,7	4,7	4,7
Density @15°C, kg/m ³	ASTM D4052	898	890	905

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.