

MOL Hydro HM 68

hydraulic oil



MOL Hydro HM 68 is a general purpose hydraulic work fluid, produced from highly refined base oils, containing a zinc based additives for reducing wear. It meets or exceeds the requirements of DIN 51524-Part 2 (HLP) of ISO 11158 (HM). It provides a reliable performance for a wide range of industrial and mobile hydraulic equipment.

Application



Hydraulic systems operating at high pressures and under heavy operating conditions

Hydraulic systems of machine-tools

Circulation systems

Hydraulic systems of machines used in the plastics industry

Turbo-, screw and vane compressors

Hydraulic systems of earthmoving and forestry machines

Features and benefits

Good wear protection

Reliable equipment protection and long machine lifetime
Contributes to increasing equipment lifetime

Good thermal and hydrolytic stability

Provides stick-free operation of servo and control valves
Low deposit formation
Long oil drain intervals
Reliable operation, so reduced operational costs

Excellent filterability

No deterioration of filterability, even in the presence of moisture
Reduced maintenance costs and environmental impact

Good water separation

Water accumulating at the bottom of the tank can be removed easily
Abnormal corrosion and wear of equipment can be prevented
Longer oil change interval and equipment lifetime

Good corrosion protection

Long-term protection of steel and non-ferrous metal parts even in the presence of moisture

Rapid air release

Reduced risk of cavitation
Outgoing air does not cause a non-typical increase in foaming
Reliable operation, giving longer equipment lifetime

Specifications and approvals

Viscosity grade: ISO VG 68
ISO 11158 HM
ISO-L-HM
DIN 51524-2 (HLP)
Cincinnati Lamb P-69
AFNOR NF-E-48603 (HM)

MOL Hydro HM 68

hydraulic oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,885
Kinematic viscosity at 40°C [mm ² /s]	66,5
Kinematic viscosity at 100 °C [mm ² /s]	8,3
Viscosity index	92
Pour point [°C]	-27
Flash point (Cleveland) [°C]	240

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101983

SAP code and packaging:

13300352	MOL Hydro HM 68 X10L	10 l plastic can
13301301	MOL Hydro HM 68 20LB	20 l plastic can (for order only)
13100454	MOL Hydro HM 68 50KG	60 l steel drum
13100455	MOL Hydro HM 68 180KG	216.5 l steel drum
13100453	MOL Hydro HM 68 860KG	IBC (for order only)
13300667	MOL Hydro HM 68 860KG R1W	IBC (for order only)
13100452	MOL Hydro HM 68	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.