


# MOL Hykomol Syntrans 75W-80

## synthetic automotive gear oil



MOL Hykomol Syntrans 75W-80 is a multigrade gear oil produced from a premium quality synthetic base oil, using a state-of-art additive system that allows an extended oil change period. Due to its unique viscosity properties, it contributes to a reduction in fuel consumption.

### Application



Manual and automatic mechanical gearboxes in modern commercial vehicles

Manual gearboxes in modern passenger cars, SUVs and light commercial vehicles

### Features and benefits

Outstanding oxidation stability

Low coefficient of friction

Excellent thermal stability

Excellent cold flow properties

Low foaming tendency

Excellent wear protection

Enables long drain interval application

Good efficiency and low fuel consumption

Prevents formation of sludge and deposits, so servicing needs are reduced

Fuel-saving operation at low temperature

Continuous, stable lubricating film, even at high speeds

Long gear lifetime, giving reliable operation

### Specifications and approvals

Viscosity grade: SAE 75W-80

MAN 341 Typ Z4

ZF TE-ML 02L[ZF001064]

ZF TE-ML 16K[ZF001064]

API GL-4

MAN 341 Typ E3

Volvo 97307

Renault

DAF

IVECO

ZF TE-ML 08

Eaton

# MOL Hykomol Syntrans 75W-80

## synthetic automotive gear oil



### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,861
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	56,5
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	9,5
Viscosity index	152
Pour point [°C]	-42
Flash point (Cleveland) [°C]	220

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101987

#### SAP code and packaging:

13301992	MOL Hykomol Syntrans 75W-80 10LA	10 l plastic can
13100207	MOL Hykomol Syntrans 75W-80 180KG	216.5 l steel drum

#### Order booking:

Please contact your local distributor or sales partner for ordering details.