


MOL Hykomol 85W-140

automotive gear oil



MOL Hykomol 85W-140 is a multigrade gear oil produced from highly refined base oils, using additives having complex effects, and having a high operating viscosity.

Application



Manual and automatic mechanical gearboxes of commercial vehicles

Manual gearboxes, gear drives of agricultural and construction machines

Final drives of agricultural and construction machines

Features and benefits

Excellent wear protection

Up-to-date additive system

Low foaming tendency

Good thermal and oxidation stability

Outstanding corrosion protection

Long gear lifetime, giving reliable operation

Efficient EP performance, giving a long life for synchronizing rings

Stable, continuous lubricating film, giving reduced wear

Excellent properties are sustained for a long time

Long-term protection of parts

Specifications and approvals

Viscosity grade: SAE 85W-140

API GL-4

MIL-L-2105

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,904
Kinematic viscosity at 40°C [mm ² /s]	425
Kinematic viscosity at 100 °C [mm ² /s]	27,2
Viscosity index	88
Pour point [°C]	-12
Flash point (Cleveland) [°C]	260

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Hykomol 85W-140

automotive gear oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C