



TECHNICAL DATA SHEET/ OILY TRANSPO 15W-40

DESCRIPTION:

OILY TRANSPO 15W-40 (SAE 15W-40) is a mineral lubricant used in petrol and diesel engine on-road applications (cars, bakkies, trucks, buses).

SPECIFICATION:

- ACEA E7-22 (2022)
- ACEA E7-16 (2016)
- API CI-4/SL
- MAN M3275
- Cummins CE20076
- Mack EOM
- MTU Type 2
- Volvo VDS-2

KEY ADVANTAGES:

- Detergent, antioxidant and anti-corrosion additives help to reach standard oil drain intervals defined by the manufacturer.
- Detergent, dispersant and anti-wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS:

PARAMETER	UNIT	METHOD	TYPICAL RESULT
Density at 20°C	kg/m ³	ASTM D1298	0.880
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	112.00
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	15.00
Viscosity Index	-	ASTM D2270	135
Flash point	°C	ASTM D92	210
Pour point	°C	ASTM D97	-30
Total Base Number	mgKOH/g	ASTM D2896	10.7
Sulphated Ash	% m/m	ASTM D874	1.45

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDED USE:

- Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the vehicle manufacturer's requirements.
- The product should not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.
- All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT:

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. It is accessible on request from your local dealer. This product should not be used for applications other than those for which it is intended. If disposing of used product, take care to protect the environment and comply with local regulations.

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.