


MOL Ultrans 220

industrial gear oil



MOL Ultrans 220 is a high performance industrial gear oil produced from highly refined base oils using additives that have combined effects. Its load carrying ability and EP effect is outstanding.

Application



High performance spur and helical, spur and spiral bevel, enclosed industrial gear drives

Gear drives exposed to shock loads

Oil lubricated sliding and rolling bearings

Mist lubrication systems

Features and benefits

Excellent load-carrying properties

Excellent protection against micropitting

Exceptional thermal and oxidation stability

Low foaming tendency

No deposit formation

Excellent water separation

Free of lead and chlorine

Excellent yellow metal compatibility

No lubricating film disruption even under shock loads, giving protection against seizure

Long gear lifetime, giving reliable operation

Resists the ageing process and deposit formation, even at high operating temperatures, giving long oil lifetimes and reduced maintenance costs

Continuous lubricating film, even at high loads

Low filtering cost and reduced downtime

Water accumulating at the bottom of the tank can be removed easily
Abnormal corrosion and wear of equipment can be prevented

Applicable in mist-lubrication systems

Fully compatible with bronze and copper metal parts

Specifications and approvals

Viscosity grade: ISO VG 220
ISO 12925-1 CKD
ISO-L-CKD
DIN 51517-3 (CLP)
AGMA 9005-E02 EP

MOL Ultrans 220

industrial gear oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,897
Kinematic viscosity at 40°C [mm ² /s]	224,9
Kinematic viscosity at 100 °C [mm ² /s]	19,0
Viscosity index	95
Pour point [°C]	-24
Flash point (Cleveland) [°C]	240
Antiwear properties (FZG)	
- failure load stage	>12

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: max. 40°C